






XPP-5460GCX

X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp with Hard Hat Clip

MARKET APPLICATIONS	Hazardous work environments, industrial, automotive, law enforcement, fire & rescue
DESCRIPTION	This X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp with Hard Hat Clip is cULus, ATEX and IECEx listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an integrated Stainless Clip for attachment to most hard hat mounting brackets. Both the spotlight and the floodlight use modern LEDs and an advanced (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern. Front mounted dual switches provide easy access to the spotlight for distance illumination, the floodlight for close-up illumination, and Dual-Light for maximum lighting, versatility and user safety. The XPP-5460GCX includes a hard hat mount for use on a fire helmet or hard-hat, and is powered by 3 AAA batteries (included).
CASE MATERIAL	Engineered Polymer - Green
DIMENSIONS	Length: 3.54 in (90 mm) • Width: 1.54 inches (40 mm) • Depth: 1.875 inches (48 mm)
WEIGHT	Weight: 5.8 oz. (166 g) with batteries installed
LENS	Unbreakable polycarbonate with scratch resistant coating
LIGHT SOURCE	LED
LIGHT OUTPUT	High-Brightness Spotlight: 180 lumens • Low-Brightness Spotlight: 100 lumens • High-Brightness Floodlight: 180 lumens • Low-Brightness Floodlight: 100 lumens • Dual-Light: 200 lumens
ON/OFF	Dual Switches. High/Low Spotlight, High/Low Floodlight, Dual-Light
RUN-TIME	High-Brightness Spotlight: 3.5 hours • Low-Brightness Spotlight: 10 hours • High-Brightness Floodlight: 3.5 hours • Low-Brightness Floodlight: 10 hours • Dual-Light: 3 hours
BATTERY	3 Alkaline AAA batteries (included)

FEATURES


- cULus, ATEX and IECEx listed Intrinsically Safe
- LED technology
- Focused high/low-brightness spotlight beam for distance illumination
- Unfocused high/low-brightness wide-beam floodlight for close-up illumination
- Dual-Light™ (spotlight and floodlight on at the same time) for maximum versatility
- Glass-filled nylon polymer housing
- (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern
- Dual switches located on front of light
- Adjustable tilt head
- Hard hat clip for fire helmets and hard hats
- Dustproof/Waterproof
- Meets the requirements of NFPA-1971-8.6 (2013)
- Impact & chemical resistant
- Powered by 3 AAA batteries (included)

FL 1 STANDARD	DUAL-LIGHT	HIGH	LOW
	200 LUMENS	180 LUMENS	100 LUMENS
	3h	3h 30 min	10h
	78m	106m	74m
	1528cd	2799cd	1399cd
	2m 1m		

WARRANTY
APPROVALS

Limited Lifetime Warranty



 cUL US LISTED E 467756 ID 4003544 INTRINSICALLY SAFE SECURITE INTRINSEQUE	Bayco Products, Inc. XPP-5460 Wylie, TX 75098
	Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G CLASS I ZONE 0 GRP IIC T4 CLASS II ZONE 20 IIIC T135°C Ⓢ II 1 G Ex ia IIC T4 Ga
Ⓢ 0359	Ex ia IIC T4 Ga DEMKO 17 ATEX 1824 IECEx UL 17.0003 -20°C ≤ Tamb ≤ +40°C 1.5V/Cell / E92 or EN92 SEE INSTRUCTION MANUAL VOIR MANUEL MFG MM-YY